Metrix+™
Innovative Excellence

WET COATING THICKNESS GAUGE

CG 3000

Precise wet film coating measurement



Applications

This is used for checking the coating thickness of wet paint, enamel lacquer, adhesive, architectural coating, color coating, varnish, chemical industry, or other coating that has been applied to a smooth surface.

Measuring procedure

1. Select comb according to approximate thickness.
2. Hold comb perpendicular to coating to be measured.
3. Press into coating until the comb stands square.
4. Wet film thickness is between the highest step coated and the next (higher) step remains uncoated.

Technical Specifications

Model	*Metrix+* CG 3000
Measuring range	25 ~ 3000um (1 ~ 118mil)
Values(um)	25, 50, 75, 100, 125, 150, 175, 200, 225, 250, 275, 300, 350, 400, 450, 500, 550, 600, 650, 700, 750, 800, 850, 900, 1000, 1100, 1200, 1400, 1600, 1800, 2000, 2200, 2400, 2600, 2800, 3000µm
Values(mil)	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14 ,16, 18, 20, 22, 24, 26, 28, 30, 31, 33, 35, 39, 43, 47, 55, 63, 71, 79, 87, 94, 102, 110, 118mil

Model and Specifications subject to change without notice.